

UL Product iQ™



XGPU2.E506488 - Thermistor-type Devices - Component

Thermistor-type Devices - Component

See General Information for Thermistor-type Devices - Component

BAODIAN (SHENZHEN) INDUSTRIAL CO LTD

E506488

18E, FUYI PAVILION, FUXING GARDEN BUILDING, NO.162 FUXING ROAD, FUHUA COMMUNITY, FUTIAN DISTRICT

SHENZHEN, GUANGDONG CHINA


PTC current limiter:

Model No.	Voltage (V)		Current (A)				T _{moa} (°C)	Class	CA
	V _{max}	V _r	I _h (mA)	I _t (mA)	I _{max} (A)	I _{sc} (A)			
PTC080515V005	15.0	15.0	0.05	0.15	30	30	85	C1	1(125), 2, 3, 4, #
PTC080515V010	15.0	15.0	0.10	0.30	30	30	85	C1	1(125), 2, 3, 4, #
PTC08059V020	9.0	9.0	0.20	0.50	30	30	85	C1	1(125), 2, 3, 4, #
PTC08056V035	6.0	6.0	0.35	0.75	30	30	85	C1	1(125), 2, 3, 4, #
PTC08056V050	6.0	6.0	0.50	1.00	30	30	85	C1	1(125), 2, 3, 4, #
PTC08056V075	6.0	6.0	0.75	1.50	35	35	85	C1	1(125), 2, 3, 4, #
PTC08056V100	6.0	6.0	1.00	1.95	35	35	85	C1	1(125), 2, 3, 4, #
PTC08056V110	6.0	6.0	1.10	2.20	35	35	85	C1	1(125), 2, 3, 4, #
PTC08056V125	6.0	6.0	1.25	2.50	35	35	85	C1	1(125), 2, 3, 4, #
PTC08056V150	6.0	6.0	1.50	3.00	35	35	85	C1	1(125), 2, 3, 4, #
PTC120660V005	24.0	24.0	0.05	0.15	10	10	85	C3	1(125), 2, 3, 4, #
PTC120660V010	24.0	24.0	0.10	0.25	10	10	85	C3	1(125), 2, 3, 4, #
PTC120660V012	24.0	24.0	0.12	0.29	10	10	85	C3	1(125), 2, 3, 4, #
PTC120624V016	24.0	24.0	0.16	0.37	10	10	85	C3	1(125), 2, 3, 4, #
PTC120624V020	24.0	24.0	0.20	0.46	10	10	85	C3	1(125), 2, 3, 4, #
PTC120624V025	24.0	24.0	0.25	0.50	10	10	85	C2	1(125), 2, 3, 4, #
PTC120616V035	6.0	6.0	0.35	0.75	35	35	85	C2	1(125), 2, 3, 4, #
PTC120616V050	6.0	6.0	0.50	1.00	35	35	85	C2	1(125), 2, 3, 4, #

PTC120616V075	6.0	6.0	0.75	1.50	35	35	85	C2	1(125), 2, 3, 4, #
PTC120616V100	6.0	6.0	1.00	1.80	35	35	85	C2	1(125), 2, 3, 4, #
PTC120616V110	6.0	6.0	1.10	2.20	35	35	85	C2	1(125), 2, 3, 4, #
PTC12066V150	6.0	6.0	1.50	3.00	35	35	85	C2	1(125), 2, 3, 4, #
PTC12066V200	6.0	6.0	2.00	3.50	35	35	85	C1	1(125), 2, 3, 4, #
PTC060330V003	9.0	9.0	0.03	0.09	20	20	85	C4	1(125), 2, 3, 4, #
PTC060315V005	9.0	9.0	0.05	0.15	20	20	85	C4	1(125), 2, 3, 4, #
PTC060315V010	9.0	9.0	0.10	0.30	35	35	85	C4	1(125), 2, 3, 4, #
PTC06039V020	9.0	9.0	0.20	0.50	35	35	85	C4	1(125), 2, 3, 4, #
PTC06039V025	9.0	9.0	0.25	0.55	35	35	85	C4	1(125), 2, 3, 4, #
PTC121060V005	13.2	13.2	0.05	0.15	30	30	85	C4	1(125), 2, 3, 4, #
PTC121060V010	13.2	13.2	0.10	0.30	30	30	85	C4	1(125), 2, 3, 4, #
PTC121030V020	13.2	13.2	0.20	0.40	30	30	85	C4	1(125), 2, 3, 4, #
PTC121016V035	13.2	13.2	0.35	0.75	30	30	85	C4	1(125), 2, 3, 4, #
PTC121013V050	13.2	13.2	0.50	1.00	30	30	85	C3	1(125), 2, 3, 4, #
PTC12106V075	6.0	6.0	0.75	1.50	30	30	85	C3	1(125), 2, 3, 4, #
PTC12106V110	6.0	6.0	1.10	2.20	35	35	85	C3	1(125), 2, 3, 4, #
PTC12106V150	6.0	6.0	1.50	3.00	35	35	85	C3	1(125), 2, 3, 4, #
PTC12106V175	6.0	6.0	1.75	3.50	35	35	85	C3	1(125), 2, 3, 4, #
PTC12106V200	6.0	6.0	2.00	4.00	35	35	85	C3	1(125), 2, 3, 4, #
PTC181260V010	33.0	33.0	0.10	0.30	30	30	85	C3	1(125), 2, 3, 4, #
PTC181260V014	33.0	33.0	0.14	0.34	30	30	85	C3	1(125), 2, 3, 4, #
PTC181230V020	33.0	33.0	0.20	0.40	30	30	85	C3	1(125), 2, 3, 4, #
PTC181230V030	33.0	33.0	0.30	0.60	30	30	85	C3	1(125), 2, 3, 4, #
PTC181230V050	33.0	33.0	0.50	1.00	30	30	85	C3	1(125), 2, 3, 4, #
PTC181213V075	13.2	13.2	0.75	1.50	30	30	85	C3	1(125), 2, 3, 4, #
PTC181216V110	8.0	8.0	1.10	2.20	35	35	85	C3	1(125), 2, 3, 4, #
PTC181216V125	8.0	8.0	1.25	2.50	35	35	85	C3	1(125), 2, 3, 4, #
PTC181216V150	8.0	8.0	1.50	3.00	35	35	85	C3	1(125), 2, 3, 4, #
PTC18128V160	8.0	8.0	1.60	2.80	35	35	85	C3	1(125), 2, 3, 4, #
PTC181216V200	8.0	8.0	2.00	4.00	35	35	85	C3	1(125), 2, 3, 4, #

PTC181216V260	8.0	8.0	2.60	5.00	35	35	85	C3	1(125), 2, 3, 4, #
---------------	-----	-----	------	------	----	----	----	----	--------------------

Indicates unique Condition of Acceptability

Marking: Company name or trademark, part designation and the Recognized Component Mark  permanently and legibly marked on individual parts or on the smallest shipping container.

Last Updated on 2019-03-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:
1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"