

# CC LUBE™

## CLEAR, CLEAN, SEMI-SYNTHETIC MULTIPURPOSE LUBRICANT

### DESCRIPTION

**CC LUBE™** is a state-of-the-art, semi-synthetic, multi-purpose lubricant that combines an aluminum complex thickener for extreme water resistance with the latest synthetic ingredients and PTFE to create a totally transparent, long-lasting, high lubricity lubricant with unequalled quality and performance.

**CC LUBE** is clear, clean, colorless, nonstaining, nondrying, biodegradable and unsurpassed in reducing friction, extending machine and equipment life and preventing the formation of rust and corrosion over a broad temperature range of 0°F (-18°C) to 400°F (204°C). **CC LUBE** is NSF (H-1) Registered for use in Federally Inspected Meat and Poultry Plants.

- Nontoxic, Nonstaining
- Clear, Clean Lubricant
- Nondrying Formula
- Colorless/Odorless
- Contains PTFE
- NSF (H-1) Registered
- Prevents Rust, Corrosion
- Biodegradable
- Extremely Water Resistant
- Reduces Friction
- Available in Other Grades

### APPLICATIONS

May be safely used on a variety of food processing equipment. **CC LUBE** is designed to eliminate hot water wash-out and has anti-bacterial additives to eliminate bacterial culturing. It may be used safely on a variety of surfaces including metal, plastic, rubber (viton, neopreen, buna & HSN), vinyl, stainless steel and nylon. **CC LUBE** is an ideal lubricant for roller, pillow block, needle and plain bearings that are used in cooking, processing and packaging of food products. It is a clear lubricant and will not stain cotton, polyester or Mylar fabrics.

Bearings	Conveyors
Bushings	Bottling equipment
Gears	Belting for baking ovens
Valves	Food processing machinery

NSF (H-1) Reg. #048221  
Conforms to FDA Regulations CFR 21 Section  
178.3570 for Incidental Food Contact.

### PRODUCT CHARACTERISTICS

Thickener	Aluminum Complex
Fluid Type	White Oils & Synthetics
Color/Appearance	Clear
Dropping Point (ASTM D-566)	500°F (260°C)
Specific Gravity	0.88
Density (lb/gal)	7.3
Additive Type	Organic, R&O, PTFE
Flash Point (ASTM D-92)	>430°F (221°C)
Autoignition Point (CALCULATED)	>500°F (260°C)
NLGI Grade	1-1½
Penetration @77°F (ASTM D-217)	285-315
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	126
Load Wear Index	25
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hours	<5.0
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	100 - 150
cSt @ 100°C	14.3 typ.

### PACKAGING

Code No.	Container Size	Container
70550	14 oz.	Cartridge
70516	35 lb.	5 gal. drum
70524	120 lb.	15 gal. drum
70529	400 lb.	50 gal. drum

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.  
4849 HOMESTEAD RD.,  
SUITE 232  
HOUSTON, TX 77028

WATS: 800-538-5823  
PHONE: 713-670-5700  
FAX: 713-678-4604  
sales@jetlube.com  
www.jetlube.com

FOODGRADE  
FOODGRADE  
FOODGRADE  
FOODGRADE  
FOODGRADE  
FOODGRADE